

Si Series Inverter Selection Chart



	Si-36	Si-125	Si-250	Si-400	Si-600
Input Voltage	Universal input	Si-125-120 Si-125-277 Model Dependent	Si-250-120 Si-250-277 Model Dependent	Si-400 120 or 277V Dual Input	Si-600 120 or 277V Dual Input
Output Power	36W	125W	250W	400W	600W
Self Testing/Self Diagnostic	Monthly and Annual Testing Illuminated Test Switch	Monthly, reported via visual user interface panel or RTS-M	Monthly, reported via visual user interface panel or RTS-M	N/A	N/A
Dimensions	13.5"L x 3.2"W x 1.18"H	14.3"L x 10.1"W x 4.1"D	17.3"L x 11.1"W x 8.6"D	18"L x 15"W x 8"D	23.25"L x 15"W x 8.25"D
Weight	3.0 Lbs	32 Lbs.	64 Lbs.	98 Lbs.	122 Lbs.
Approvals	UL Listed to UL 924	UL Listed to UL924	UL Listed to UL 924	ETL Listed to UL924	ETL Listed to UL924
Special Features	Power Share Technology No ALCRs needed for line voltage or 0-10 dimming	Wall Mount Standard Ceiling mounting Optional	Wall Mount	Wall Mount	Wall Mount

04032020