

L10 Series

10 Watt UL Listed L10-CEC, L10-DC-CEC, L10-NP-CEC
LED Emergency Drivers



Specifiers reference:

Project: _____

Type: _____

Model #: _____

Comments: _____

Product Summary

Approvals	UL Listed to UL924
Input	(Universal) 115 - 277Vac, 50/60 Hz
Input current	60 mA (max.)
Input power	4 Watts (max.)
Output voltage	15-55 Vdc - Class 2 Compliant
Output power	10W Constant Power
Operating time	90 minutes
Battery	Lithium
Test Switch	Quick Connect IP65 rated illuminated test switch
Weight	1.3 lbs. Non-conduit model 2.0 lbs. Dual conduit model 1.5 lbs. Narrow Profile case, No flex conduit
Case	Galvanized steel
Dimensions	9.5" L x 1.7" W x 1.14" H 16.53" L x 1.21" W x 1.1"H (Narrow Profile Model)
Operating Temperature	32° to 131° F (0° to 55° C)
Recharge time	24 Hrs
Warranty	5 years full

Description

The Assurance Emergency Lighting L10 Series of LED emergency drivers are used with LED luminaires and Class 2 LED drivers to convert lighting fixtures for emergency lighting applications. L10 Series LED Emergency Drivers are available with no flex conduit, dual flex conduit, and narrow profile cases.


Specifications

Emergency lighting shall be provided by using a standard LED fixture, separate LED Class 2 driver and a constant power L10 Series 10W emergency LED Driver. The LED emergency driver shall be UL Listed for field or factory installations. It allows the LED luminaire to be used for both normal and emergency operation. The luminaire can be used for switched or unswitched applications. The L10 Series of emergency drivers contains battery, charger and DC converter in a metal can and is available in 3 configurations for use in different mounting situations and ease of installation. The L10 Series emergency driver shall provide a constant 10 watts to the LED load for a minimum of 90 minutes. A quick connect IP65 rated test switch shall be included. The L10 Series shall have 4 watts of input power (max). The L10 Series meets or exceeds all National Electrical Code and Life Safety Code Emergency Lighting requirements and is rated for damp locations. The L10 Series of LED emergency drivers are warranted for a full 5 years from date of purchase. The L10 Series meets Title 20 CEC requirements.




Mounting Configurations

L10-CEC: No flex conduit



L10-DC-CEC: Dual Flex conduit



L10-NP-CEC:



Note: Output current of AC driver must not exceed 5.0A

All Specifications subject to change without prior notification.

Assurance Emergency Lighting, a division of Assurance Engineering LLC

Assurance Engineering LLC · 357 Cumberland Street · Memphis, TN 38112 · 1-877-774-4775 · www.assurancelighting.com