

L5-CEC

5 Watt UL Listed LED Emergency Driver



Specifiers reference:

Project: _____

Type: _____

Model #: _____

Comments: _____

Product Summary

Approvals	UL Listed to UL924
Input	(Universal) 115 - 277Vac, 50/60 Hz
Input current	60 mA (max.)
Input power	4 Watts (max.)
Output voltage	15-55 Vdc - Class 2 Compliant
Output power	5W Constant Power
Operating time	90 minutes
Battery	Lithium
Test Switch	Quick Connect IP65 rated illuminated test switch
Weight	1.2 lbs.
Case	Galvanized steel
Dimensions	9.5" L x 1.7" W x 1.14" H
Operating Temperature	32° to 131° F (0° to 55° C)
Recharge time	24 Hrs
Warranty	5 years full

Description

The Assurance Emergency Lighting L5-CEC Constant Power LED emergency drivers are used with LED luminaires and Class 2 LED drivers to convert lighting fixtures for emergency lighting applications.

Specifications

Emergency lighting shall be provided by using a standard LED fixture, separate LED Class 2 driver and a Constant Power L5-CEC 5W emergency LED Driver. The LED emergency driver shall be UL Listed for field or factory installation. It allows the LED luminaire to be used for both normal and emergency operation. The luminaire can be used for switched or unswitched applications. The L5-CEC LED emergency driver contains a battery, charger and DC converter in a metal can. A quick connect IP65 rated test switch shall be included. The L5-CEC LED emergency driver shall provide a constant 5 watts to the LED load for a minimum of 90 minutes. The L5-CEC shall have 4 watts of input power (max). The L5-CEC meets or exceeds all National Electrical Code and Life Safety Code Emergency Lighting requirements and is rated for damp locations. The L5-CEC LED emergency driver is warranted for a full 5 years from date of purchase. The L5-CEC meets Title 20 CEC requirements.



Mounting Configurations

L5-CEC: No flex conduit



Note: Output current of AC driver must not exceed 5.0A

All Specifications subject to change without prior notification.